

Pica P550

Anti-graffiti Coating Pigmented



Generally:

Pica Protector 550 is a wax based water borne anti-graffiti coating system that protects the surface effectively against spray and Marker Pen graffiti. Pica Protector 550's unique formula gives you a protective coating while at the same time it gives the treated surface a splash of colour.

Use:

Pica Protector 550 can be used on most types of porous surfaces that needs a splash of colour. Recommended surface temperature: +40 - +5 ° centigrade.

Directions for use:

Application

- Clean surface thoroughly.
- Coat surface evenly with Pica Protector 550. Work from the bottom of the facade to the top of the facade. Apply a second coat when first coat is dry. The facade is now effectively protected.

Cleaning

- Remove the graffiti with a high pressure cleaner at 70 bar at a temperature of 70 ° Celsius.
- Re-protect with one to two coatings of Pica Protector 550.

Solution to be used:

Concentrate (pH 8,5).

Estimated amount to be used:

Varies according to the surface. In General estimate the following;

Painted surfaces, natural stone	0.20L/m ²
Concrete, Brick	0,30L/m ²
Render	0,40L/m ²

Personal protective measures:

Not needed.

Labelling:

Not classified as hazardous goods.

Storage/durability:

Store dark and frost free. Durability, about 24 months in sealed original container.

Technical data:

Contains:	Montan waxes
Appearance:	Milky white liquid
Odour:	Neutral

The information supplied is only intended to be used as a guideline. Pica Kemi AB therefore accepts no liability based on this information on behalf of the user.