Pica T3

Alakaline facade Cleaner ECO





Generally:

Pica T3 is a low foaming, water based alkaline Façade Cleaner that conforms to the very highest environmental standards.

Use:

Pica T3 is used to remove soot, grime and air pollution in an environmentally friendly way. Pica T3 can be used on both porous and non-porous surfaces such as, brick, concrete, natural stone, tiles, metal and plastic surfaces. Pica T3 also removes soot and other carbon residues after fires.

Directions for use:

Application

- -Spray a diluted Pica T3 solution on to surface (see recommended solution below).
- -Allow 2-10 minutes for the solution to dissolve the contamination.
- -To increase efficiency on very contaminated surfaces apply a brush and "work" the surface with the brush.

Cleaning

- -Rinse with hot water and high pressure.
- -Repeat treatment if all contamination was not completely removed.
- -Please note that cold weather (temperatures below +5°C) will increase time needed to dissolve contamination.

Recommended solutions to be used

Normal: 1-10

Heavy and soot cleaning: 1-5

Extreme: concentrate

Solution to be used:

Concentrate (pH 13) or diluted.

Estimated amount to be used:

0.01-0.02 litre/m2

Personal protective measures:

Use protective goggles. Use safety gloves. Use work clothes.

Labelling:



Storage/durability:

Store dark and frost free. Durability, about 24 months in sealed original container.

Technical data:

Contains: Potassium Hydroxide,

surfactants et. al

Appearance: Transparent liquid

Odour: Neutral



The information supplied is only intended to be used as a guideline. Pica Kemi AB therefore accepts no liability based on this information on behalf of the user.